

## 6.144Gb/s BIDI SFP+ 1270nm/1330nm Transceiver (V1.0)



The 1270nm/1330nm 6.144Gb/s 10km transceiver is designed to transmit and receive serial optical data links up from 2.5 to 6.144Gb/s data rate over single-mode fiber. The transceiver is compliant with SFF-8432, and applicable portions of SFF-8431. Digital diagnostics functions are available via a 2-wire serial interface, as specified in SFF-8472.

### Features

- Compliant to SFP+ MSA
- Fully RoHS Compliant
- Operating data rate 2.5 to 6.144Gb/s
- Transmission distance up to 10km
- 1270nm/1330nm DFB Laser
- LC single connector
- Hot pluggable 20pin connector
- Wide temperature range
- Low power consumption <1.0W
- Single +3.3V±5% power supply
- Digital monitoring SFF-8472 Rev 10 compliant

### Applications

- OBSAI rates 3.072 Gb/s, 6.144Gb/s
- CPRI rates 2.4576 Gb/s, 4.9152Gb/s, 6.144Gb/s

### Standards

- SFF-8431 Rev 4
- SFF-8472 Rev 10

### Specifications

(Tested under recommended operating conditions, unless otherwise noted)

Parameter	Symbol	Unit	Min	Typ	Max	Note
Optical Transmitter Characteristics						
Data Rate	-	Gbps	2.5		6.144	
Transmission Distance	L	km			10	
Center Wavelength	$\lambda$	nm	1260	1270	1280	
			1320	1330	1340	
Spectral width(-20dB)	$\Delta\lambda_{rms}$	nm			1	1
SMSR	-	dB	30			
Optical Output Power	$P_O$	dBm	-8.2		+0.5	2
Optical Modulation Amplitude	$P_{OMA}$	dBm	-5.2			
Average Launch Power of OFF Transmitter	$P_{OFF}$	dBm			-30	
Extinction Ratio	ER	dB	3.5			
Relative Intensity Noise	$R_{IN}$	dB/Hz			-128	
Optical Output Eye	-	-	Compliant with IEEE 802.3ae			
Optical Receiver Characteristics						
Data Rate	-	Gbps	2.5		6.144	
Center Wavelength	$\lambda_C$	nm	1320	1330	1340	
			1260	1270	1280	
Receiver Sensitivity	$R_{SEN}$	dBm			-14.4	3
Receiver Overload	-	dBm	0.5			3
Receiver Reflectance	$R_{REFL}$	dB			-12	
LOS	Optical Assert	$LOS_A$	dBm	-30		
	Optical Dessert	$LOS_D$	dBm		-15	
LOS Hysteresis	-	dB	0.5		6	
Note 1: Spectral width has to be defined over -20dBm.						
Note 2: Minimum output optical level is at end of life.						
Note 3: Sensitivity for PRBS 2 <sup>7</sup> -1 and BER better than or equal to 10 <sup>-12</sup> .						

## 6.144Gb/s BIDI SFP+ 1270nm/1330nm Transceiver (V1.0)

### Ordering Information

Part No.	Specifications									Application
	Package	Data rate	Laser	Optical Power	Detector	Sensitivity	Temp	Reach	Others	
RTXM228-661	SFP+	2.5~6.144Gb/s	1270nm DFB	-8.2~ +0.5dBm	1330nm PIN	<-14.4dBm	-40~85 °C	10km	DDM	OBSAI/CPRI
RTXM228-662	SFP+	2.5~6.144Gb/s	1330nm DFB	-8.2~ +0.5dBm	1270nm PIN	<-14.4dBm	-40~85 °C	10km	DDM	OBSAI/CPRI
RTXM228-663	SFP+	2.5~6.144Gb/s	1270nm DFB	-8.2~ +0.5dBm	1330nm PIN	<-14.4dBm	0~70 °C	10km	DDM	OBSAI/CPRI
RTXM228-664	SFP+	2.5~6.144Gb/s	1330nm DFB	-8.2~ +0.5dBm	1270nm PIN	<-14.4dBm	0~70 °C	10km	DDM	OBSAI/CPRI

### Absolute Maximum Ratings

Parameter	Symbol	Unit	Min	Max
Storage Temperature Range	Ts	°C	-40	85
Relative Humidity	RH	%	5	95
Supply Voltage	V <sub>CC</sub>	V	-0.3	4.0

### Recommended Operating Conditions

Parameter	Symbol	Unit	Min	Typ	Max
Operating Case Temperature Range	Tc	°C	-40		85
			0		70
Power Supply Voltage	V <sub>CC</sub>	V	3.14	3.3	3.46
Bit Rate	BR	Gb/s	2.5		6.144
Bit Error Ratio	BER				10 <sup>-12</sup>
Max Supported Link Length	L	km			10

### Principle diagram

