

6.144Gb/s BIDI SFP+ 1270nm/1330nm Transceiver (V1.0)



The 1270nm/1330nm 6.144Gb/s 20km transceiver is designed to transmit and receive serial optical data links up from 2.5 to 6.144Gb/s data rate over single-mode fiber. The transceiver is compliant with SFF-8432, and applicable portions of SFF-8431. Digital diagnostics functions are available via a 2-wire serial interface, as specified in SFF-8472.

Features

- Compliant to SFP+ MSA
- Fully RoHS Compliant
- Operating data rate 2.5 to 6.144Gb/s
- Transmission distance up to 20km
- 1270nm/1330nm DFB Laser
- LC single connector
- Hot pluggable 20pin connector
- Wide temperature range
- Low power consumption <1.0W
- Single +3.3V±5% power supply
- Digital monitoring SFF-8472 Rev 10 compliant

Applications

- OBSAI rates 3.072 Gb/s, 6.144Gb/s
- CPRI rates 2.4576 Gb/s, 4.9152Gb/s, 6.144Gb/s

Standards

- SFF-8431 Rev 4
- SFF-8472 Rev 10

Specifications

(Tested under recommended operating conditions, unless otherwise noted)

Parameter	Symbol	Unit	Min	Typ	Max	Note
Optical Transmitter Characteristics						
Data Rate	-	Gbps	2.5		6.144	
Transmission Distance	L	km			20	
Center Wavelength	λ	nm	1260	1270	1280	
			1320	1330	1340	
Spectral Width(-20dB)	$\Delta\lambda_{rms}$	nm			1	1
SMSR	-	dB	30			
Optical Output Power	P_O	dBm	-2		+5	2
Average Launch Power of OFF Transmitter	P_{OFF}	dBm			-30	
Extinction Ratio	ER	dB	3.5			
Relative Intensity Noise	R_{IN}	dB/Hz			-128	
Optical Output Eye	-	-	Compliant with IEEE 802.3ae			
Optical Receiver Characteristics						
Data Rate	-	Gbps	2.5		6.144	
Center Wavelength	λ_C	nm	1320	1330	1340	
			1260	1270	1280	
Receiver Sensitivity	R_{SEN}	dBm			-14.4	3
Receiver Overload	-	dBm	0.5			3
Receiver Reflectance	R_{REFL}	dB			-12	
LOS	Optical Assert	LOS_A	dBm	-30		
	Optical Dessert	LOS_D	dBm			-15
LOS Hysteresis	-	dB	0.5		6	
Note 1: Spectral width has to be defined over -20dBm.						
Note 2: Minimum output optical level is at end of life.						
Note 3: Sensitivity for PRBS 2 ⁷ -1 and BER better than or equal to 10 ⁻¹² .						

6.144Gb/s BIDI SFP+ 1270nm/1330nm Transceiver (V1.0)

Ordering Information

Part No.	Specifications									Application
	Package	Data rate	Laser	Optical Power	Detector	Sensitivity	Temp	Reach	Others	
RTXM228-665	SFP+	2.5~6.144Gb/s	1270nm DFB	-2~ +5dBm	1330nm PIN	<-14.4dBm	-40~85 °C	20km	DDM	OBSAI/CPRI
RTXM228-666	SFP+	2.5~6.144Gb/s	1330nm DFB	-2~ +5dBm	1270nm PIN	<-14.4dBm	-40~85 °C	20km	DDM	OBSAI/CPRI
RTXM228-667	SFP+	2.5~6.144Gb/s	1270nm DFB	-2~ +5dBm	1330nm PIN	<-14.4dBm	0~70 °C	20km	DDM	OBSAI/CPRI
RTXM228-668	SFP+	2.5~6.144Gb/s	1330nm DFB	-2~ +5dBm	1270nm PIN	<-14.4dBm	0~70 °C	20km	DDM	OBSAI/CPRI

Absolute Maximum Ratings

Parameter	Symbol	Unit	Min	Max
Storage Temperature Range	Ts	°C	-40	85
Relative Humidity	RH	%	5	95
Supply Voltage	V _{CC}	V	-0.3	4.0

Recommended Operating Conditions

Parameter	Symbol	Unit	Min	Typ	Max
Operating Case Temperature Range	Tc	°C	-40		85
			0		70
Power Supply Voltage	V _{CC}	V	3.14	3.3	3.46
Bit Rate	BR	Gb/s	2.5		6.144
Bit Error Ratio	BER				10 ⁻¹²
Max Supported Link Length	L	km			20

Principle diagram

